

EVERPURE° FC-S FILTER CARTRIDGES

DELIVER PREMIUM QUALITY DRINKING WATER FOR ICE AND STEAM APPLICATIONS

4FC-S Replacement Cartridge 1 PK: EV9692-31 7FC-S Replacement Cartridge 1 PK: EV9692-71



APPLICATIONS

Ice

Steam and Combi Ovens

Coffee

FEATURES • BENEFITS

Integrated beaded phosphate with levels specifically selected for greater life and scale inhibition

Proprietary Micro-Pure® II filtration media effectively inhibits the growth of bacteria on the filter media that can decrease product life

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

Exclusive precoat filtration provides superior chlorine taste and odor reduction and micro-filters dirt and particles as small as 0.5 micron in size by mechanical means

NSF/ANSI Standard 53 certified to reduce cysts such as Cryptosporidium and Giardia by mechanical means

Balanced cartridge for optimum performance in varying water qualities.

Compatible with Insurice®, Insurice PF, QC7I, QL2, QL3B and QL3 Heads

Reduces chlorine taste and odor and other offensive contaminants that can adversely affect the taste of beverages

Protects drink system seals, pump, tubing and small orifices from clogging, corrosion and abrasive wear

INSTALLATION TIPS

Install vertically so cartridge hangs down

Allow 2-1/2" (6.35 cm) clearance below the cartridge for easy cartridge replacement

Flush cartridge by running water through system for five (5) minutes at full flow

OPERATION TIPS

Replace cartridge when flow rate becomes inconveniently slow or before rated capacity is reached. It is recommended to replace cartridge at least once per year

Change cartridges when capacity is reached or when pressure falls below 10 psi (0.7 bar)

Always flush the filter cartridge at time of installation and cartridge change

SIZING


Service Flow Rate: 2.5 gpm (9.5 Lpm)

Rated Capacity:

4FC-S: 15,000 gallons (56,781 L) 7FC-S: 25,000 gallons (94,635 L)

EVERPURE® FC-S FILTER CARTRIDGES

4FC-S FV9692-31 • 7FC-S FV9692-71



SPECIFICATIONS

Overall Dimensions

4FC-S: 14.5" L x 3.25" dia. (36.8 x 8.3 cm) 7FC-S: 20.75" L x 3.25" dia (52.7 x 8.3 cm)

Service Flow Rate

Maximum 2.5 gpm (9.5 Lpm)

Rated Capacity

4FC-S: 15,000 gallons (56,781 L) 7FC-S: 25,000 gallons (94,635 L)

Pressure Requirements

10 - 125 psi (0.7 - 8.6 bar), non-shock

Maximum Temperature

35 - 100°F (2 - 38°C)

Electrical Connection

None



Cartridges Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42 — Aesthetic Effects

Bacteriostatic Effects

Chemical Reduction

Taste and Odor

Chlorine

Mechanical Filtration
Nominal Particulate Class 1

Standard No. 53 — Health Effects

Cvst

Mechanical Filtration Turbidity

EPA No. 002623-IL-002

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

WARRANTY

Everpure water treatment systems by Pentair® (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.



FILTRATION & PROCESSING SOLUTIONS

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA • WWW.EVERPURE.COM 800.942.1153 MAIN [US ONLY] • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO AUSTRALIA / NEW ZEALAND, 1-21 MONASH DRIVE, DANDENONG SOUTH, VIC, 3175, AUSTRALIA 1300.576.190 TEL • AU.EVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO CHINA, 21F CLOUD 9 PLAZA, NO 1118, SHANGHAI, 200052, CHINA

86.21.3211.4588 TEL • 86.21.3211.4580 FAX • CHINA.WATER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO INDIA, GREEN BOULEVARD, B-9/A, 7TH FLOOR - TOWER B SECTOR 62, NOIDA - 201301

91.120.419.9444 TEL • 91.120.419.9400 FAX • INDIACUSTOMER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO EUROPE, PENTAIR WATER BELGIUM BVBA, INDUSTRIEPARK WOLFSTEE, TOEKOMSTLAAN, 30 B-2200 HERENTALS, BELGIUM +32.(0).14.283.500 TEL • +32.(0).14.283.505 FAX • SALES@EVERPURE-EUROPE.COM EMAIL

EVERPURE-SHURFLO JAPAN INC., HASHIMOTO MN BLDG. 7F, 3-25-1 HASHIMOTO, MIDORI-KU, SAGAMIHARA-SHI KANAGAWA 252-0143, JAPAN 81.(0)42.775.3011 TEL • 81.(0)42.775.3015 FAX • INFO@EVERPURE.CO.JP EMAIL

EVERPURE-SHURFLO SOUTHEAST ASIA, 390 HAVELOCK ROAD, #04-01, KING'S CENTRE, SINGAPORE 169662 65.6795.2213 TEL • FAX: 65.6795.2219 FAX • CSEVERPURE@PENTAIR.COM EMAIL

All Pentair trademarks and logos are owned by Pentair, Inc. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

© 2014 Pentair Filtration Solutions, LLC EV9692-31-71 MR14